



A0115337 - 70' 2008 TEREX TC-65; 2009 FORD F750 4X2

Warehouse: N13 - NRU - TEREX - STOCKTON CA

CHASSIS SPECIFICATIONS

VIN: 3FRXF75T39V116857
Engine Make / HP: CAT /
Transmission: AUTOMATIC
Brakes: AIR
Hitch: 15 TON PINTLE
Winch Location: N/A **Capacity:** N/A
Drive Type: NON-AWD **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:

EQUIPMENT SPECIFICATIONS

Serial Number: 2080836942
Working Height: 70' **Capacity:** 700LBS
Bucket: 24X48X42 2-MAN
Certified Kv: 46KV CAT C
Rotation: CONTINUOUS
Outrigger(s): (2) SETS A FRAME
Mount: OVER REAR AXLE
Tool Circuit: DUAL HYD AT PLATFORM
Controls: SINGLE STICK
Body: UTILITY LINE
Winch/Jib: HYD EXT JIB/WINCH **Capacity:** 1,500LBS
Additional: N/A
Over Center: N **Telescoping:** N **Upper Controls:** Y
Rotator: Y **Material Handler:** Y **Insulated Boom:** Y

DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 12'6" **Length:** 35'8" **Width:** 8'6"
GVWR: 33,000 **Unladen:** 25,500LBS **Tow Capacity:**
Axle Capacity: 12,000LBS front / 21,000LBS rear
Wheelbase: 194 WB / 138 CA **Tire Size:**
Tread Front/Rear: 12/32: 18/32 **Tread Updated:** 10/25/2018
PTO Hours: 3329
Engine Hours: 6,181 **Hours Updated:** 12/13/2019
Miles: 52,360 **Miles Updated:** 12/13/2019

Insurance Value: \$65,900.00

Additional Specs:

70' 08 TEREX TC65-MH; 09 FORD F750 4X2 A0115337 EQUIP DESC: 41.8 FT. OF HORIZONTAL REACH, POWER ASSIST CONTROL SYSTEM, LOWER BOOM ARTICULATION IS FROM 0 DEGREES TO 100 DEGREES, (2) INTEGRAL HOLDING VALVES, PRESSURE IS 3000 PSI, 35 GALLON HYDRAULIC OIL, 100 MESH FILTER, SHUT OFF VALVE, PLATFORM LEVELING, HYD PLATFORM TILT, BOOM INTERLOCK, PEDESTAL, SHEAR-BALL ROTATION BEARING, AUXILIARY LET DOWN, INSULATED ENGINE STOP/START, TIE DOWN KIT, AUXILIARY TOOL OUTLETS, 69 KV CAT B OPTION TRUCK DESC: 30 LONG TAIL SHELF, 7-LAMP LIGHT BAR AT REAR, ICC REAR BUMPER, COMPARTMENT W/SIDE VERTICAL DOOR, GRAB HANDLE, POOL TYPE PIPE GRAB, 24X24X2-1/4 LAMINATED WOOD OUTRIGGER PAD W/ROPE HANDLE, OUTRIGGER PAD STORAGE BRACKETS, RUBBER WHEEL CHOCKS, PETERSON 7-LAMP DOT LIGHTING PACKAGE, AMBER STROBE LIGHT, 7-PRONG TRLR SOCK, POWER TAKE OFF, DOT INSPECTION, REMOTE ENGINE STOP/START CONTROL, B/U ALARM, BRACKET FOR STORNG GROUNDING CABLE, 2/0 BLACK GROUND CABLE 50' OF MULTI-STRAND FLEXIBLE COPPER CABL

