



A0115037 - 55' 2007 TEREX TL-50; 2008 INTERNATIONAL 7300 4X4

Warehouse: N63 - NRU - NESCO - BAKERSFIELD

CHASSIS SPECIFICATIONS

VIN: 1HTWBAAN38J667142
Engine Make / HP: INTL DT466 / 245
Transmission: ALLISON 3000RDS 5-SPEED A
Brakes: AIR
Hitch: 15 TON PINTLE HOOK
Winch Location: Capacity:
Drive Type: ALL WHEEL DRIVE **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:



EQUIPMENT SPECIFICATIONS

Serial Number: 2071234782
Working Height: 55' **Capacity:** 600 LBS
Bucket: 24X48X42 2-MAN
Certified Kv: 46KV CAT C
Rotation: CONTINUOUS
Outrigger(s): (2) SETS A FRAME
Mount: OVER REAR AXLE
Tool Circuit: HYD AT PLATFORM
Controls: SINGLE STICK
Body: UTILITY LINE
Winch/Jib: HYD EXT JIB WINCH **Capacity:** 1,500LBS
Additional:
Over Center: N **Telescoping:** Y **Upper Controls:** Y
Rotator: Y **Material Handler:** Y **Insulated Boom:** Y



DIMENSIONS / MILES / HOURS / WEIGHTS

Height: **Length:** **Width:**
GVWR: 33,000 **Unladen:** 24,700LBS **Tow Capacity:**
Axle Capacity: 12,000LBS front / 21,000LBS rear
Wheelbase: WB / 120 CA **Tire Size:** 11R22.5
Tread Front/Rear: **Tread Updated:**
PTO Hours: 3081
Engine Hours: 6,057 **Hours Updated:** 10/30/2019
Miles: 45,509 **Miles Updated:** 10/30/2019



Insurance Value: \$64,500.00

Additional Specs:

55' 07 TEREX TL50M; 08 IH 7300 4X4 A0115037 EQUIP DESC: PLATFORM REST, PLATFORM LEVELING, LOWER CONTROLS CONSTRUCTED OF HIGH STRENGTH STEEL AND LOCATED ON TURNABLE, UPPER BOOM CONSTRUCTED OF HIGH STRENGTH STEEL, LOWER BOOM CYLINDER, UPPER BOOM CYLINDER, EXTENSION CYLINDER, TWO SPEED ENGINE THROTTLE CONTROL, BOOM INTERLOCK, PEDESTAL W/ 20 GALLON TANK, TURNTABLE, SHEAR BALL BEARING ROTATION, HYDRUALIC PUMP, AUXILIARY LET DOWN, INSULATED ENGINE STOP/START, SPRING LOADED PLATFORM REST, INSULATED PLATFORM LINER, VINYL PLATFORM COVER TRUCK DESC: TAIL SHELF 30 W/ 12 GAUGE TREADPLATE, 7-LAMP LIGHT BAR AT REAR, LAMINATED WOOD OUTRIGGER PAD, OUTRIGGER PAD STORAGE, HYDRAULIC PUMP, POWER TAKE OFF, PETERSON 7-LAMP DOT LIGHTING PACKAKGE, REMOTE START/STOP CONTROL FROM REAR OF VEHICLE, PUSH BUTTON THROTTLE CONTROL, 50' COPPER GROUND CABLE, 6-PRONG TRAILER SOCKET