



**A0115332 - 70' 2006 TEREX TC-65; 2007 FORD F750 4X2**

Warehouse: N21 - NRU - CRANE TECH - BEAUMONT T

**CHASSIS SPECIFICATIONS**

**VIN:** 3FRXF75T27V514607  
**Engine Make / HP:** 7.2L CAT 6 CYL / 250  
**Transmission:** ALLISON 06K25 AUTO  
**Brakes:** AIR  
**Hitch:** 15 TON PINTLE  
**Winch Location:** N/A **Capacity:** N/A  
**Drive Type:** NON-AWD **Fuel Type:** DIESEL **Rail Gear:** N  
**Rail Gear Type:**

**\* NOT C.A.R.B COMPLIANT \***



**EQUIPMENT SPECIFICATIONS**

**Serial Number:** 2061232613  
**Working Height:** 70' **Capacity:** 700LBS  
**Bucket:** 24X48X42 2-MAN  
**Certified Kv:** 46KV CAT C  
**Rotation:** CONTINUOUS  
**Outrigger(s):** (2) SETS A FRAME  
**Mount:** OVER REAR AXLE  
**Tool Circuit:** DUAL HYD AT PLATFORM  
**Controls:** SINGLE STICK  
**Body:** UTILITY LINE  
**Winch/Jib:** HYD EXT JIB/WINCH **Capacity:** 1,500LBS  
**Additional:** N/A  
**Over Center:** N **Telescoping:** N **Upper Controls:** Y  
**Rotator:** Y **Material Handler:** Y **Insulated Boom:** Y

**DIMENSIONS / MILES / HOURS / WEIGHTS**

**Height:** 12'6" **Length:** 35'8" **Width:** 8'6"  
**GVWR:** 33,000 **Unladen:** 28,560LBS **Tow Capacity:**  
**Axle Capacity:** 12,000LBS front / 21,000LBS rear  
**Wheelbase:** 212 WB / 138 CA **Tire Size:** 11R22.5  
**Tread Front/Rear:** **Tread Updated:**  
**PTO Hours:** 5525  
**Engine Hours:** 8,655 **Hours Updated:** 1/30/2020  
**Miles:** 44,721 **Miles Updated:** 06/24/2020



**Insurance Value: \$74,900.00**

**Additional Specs:**

70' 06 TEREX 6TC65-MH; 07 FORD F750 4X2 A0115332 EQUIP DESC: 41.8 FT. OF HORIZONTAL REACH, CONTROL SYSTEM, LOWER BOOM ARTICULATION ENVELOPED IS FROM 0 DEGREES TO 100 DEGREES, (1) DOUBLE ACTING HYDRAULIC CYLINDER, TWO (2) INTEGRAL HOLDING VALVES, OPERATING PRESSURE IS 3000 PSI, 35 GALLON HYDRAULIC OIL RESERVOIR, 100 MESH FILTER AND SHUT OFF VALVE POWER ASSIST CONTROL SYSTEM, UPPER & LOWER CONTROLS, 2-SPEED ENGINE THROTTLE CONTROL, PLATFORM LEVELING & HYD TILT, HIGH STRENGTH STEEL UPPER & LOWER BOOM, BOOM INTERLOCK, PEDESTAL & TURNABLE, SHEAR-BALL ROTATION BEARING, CLOSED-CENTER HYD SYSTEM, AUXILIARY LET DOWN, INSULATED ENGINE STOP/START, POWER TAKE OFF, ELECTRICAL MINI-BOX SYSTEM, AUXILIARY TOOL OUTLETS AT REAR, HYD OIL COOLER WITH THERMO DYNAMIC FAN, SINGLE CONDUCTOR WIRE HOLDER TRUCK DESC: 30 TAIL SHELF, ICC REAR BUMPER, 24X24X2-1/4 LAMINATED WOOD OUTRIGGER PAD W/ROPE HANDLE, OUTRIGGER PAD STORAGE BRACKETS, DOT INSPECTION, B/U ALARM, AMBER STROBE LIGHT, 6-PRONG TRLR SOCKET,