



A0116722 - 60' 2012 TEREX TC-55; 2013 FREIGHTLINER M2 106 4X4

Warehouse: N63 - NRU - NESCO - BAKERSFIELD

CHASSIS SPECIFICATIONS

VIN: 3ALDCXDT3DDBJ5721
Engine Make / HP: 6.7L CUMMINS ISB / 250
Transmission: ALLISON 3500RDS 5-SPEED A
Brakes: AIR
Hitch: 15 TON PINTLE HOOK
Winch Location: N/A **Capacity:** N/A
Drive Type: ALL WHEEL DRIVE **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:



EQUIPMENT SPECIFICATIONS

Serial Number: 2121047739
Working Height: 60' **Capacity:** 700 LBS
Bucket: 24X48X42 2-MAN
Certified Kv: 46KV CAT C
Rotation: CONTINUOUS
Outrigger(s): (2) SETS A FRAME
Mount: OVER REAR AXLE
Tool Circuit: DUAL HYD AT PLATFORM
Controls: SINGLE STICK
Body: UTILITY LINE
Winch/Jib: HYD EXT JIB WINCH **Capacity:** 2,000LBS
Additional: N/A
Over Center: N **Telescoping:** N **Upper Controls:** Y
Rotator: Y **Material Handler:** Y **Insulated Boom:** Y



DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 12' 9" **Length:** 29' 10" **Width:** 8' 6"
GVWR: 33,000 **Unladen:** 26,340LBS **Tow Capacity:**
Axle Capacity: 12,000LBS front / 21,000LBS rear
Wheelbase: 190 WB / 120 CA **Tire Size:** 12R22.5
Tread Front/Rear: 100% **Tread Updated:** 12/12
PTO Hours: 273
Engine Hours: 6,756 **Hours Updated:** 3/16/2020
Miles: 55,821 **Miles Updated:** 06/02/2020



Insurance Value: \$112,500.00

Additional Specs:

60' 12 TEREX TC55-MH; 13 FL M2106 4X4 A0116722 EQUIP DESC: NON-OVERCENTER, LWR CONTROLS ON TURNTABLE, ENGINE THROTTLE ADVANCE, PLATFORM LEVELING, HYD PLATFORM TILT, BOOM COMPENSATION SYSTEM, BOOM INTERLOCK, ROTATION BEARING IS A HEAVY DUTY SHEAR BALL BEARING UTILIZING POLISHED ALLOY STEEL BALLS, 2500PSI CLOSED-CENTER PARALLEL-CIRCUIT HYD SYSTEM, 35-GAL HYD OIL RESERVOIR, 30 PEDESTAL, INSULATED PLATFORM LINER, VINYL PLATFORM COVER, PLATFORM REST SADDLE W/A PADDED REST, AUX LET DOWN, INSULATED ENGINE STOP/START, CHASSIS CONTROLLER, COMPONENTS TO MEET ANSI CATEGORY B RATING ILO STANDARD CAT C, 1/2 X 75' WINCH LOAD LINE W/SWIVEL HOOK & LATCH, WINCH CONTROL AT LWR CONTROLS, CONTROLS FOR 2 SETS OUTRIGGERS W/AUX TOOL OUTLETS, AUTOMATIC BOOM LATCH, B/U ALARM, 4 OUTRIGGER PADS W/ROPE HANDLE, 4 RUBBER WHEEL CHOCKS W/EYE BOLT, BRACKET FOR STORING GROUNDING CABLE, 2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING, 50' MULTI-STRAND FLEXIBLE COPPER CABLE, 3 GROUNDING LUGS, 2 FERRULES & GROUNDIN