



B0115257 - 2008 TEREX COMMANDER 4047; 2008 FORD F750 4X2

Warehouse: N15 - NRU - TEREX - SEATTLE WA

CHASSIS SPECIFICATIONS

VIN: 3FRWF75E78V679759
Engine Make / HP: 7.2L CAT / 250
Transmission: 5-SPEED AUTO
Brakes: AIR
Hitch: 15 TON PINTLE
Winch Location: N/A **Capacity:** N/A
Drive Type: NON-AWD **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:

EQUIPMENT SPECIFICATIONS

Serial Number: 2080736952
Boom Capacity: 24630LB
Rotation: CONTINUOUS
Outrigger(s): 2 SETS A FRAME
Mount: OVER REAR AXLE
Body: UTILITY LINE
Sheave Height: 47"
Auger: 20 STEEL
Dig Speed: 2-SPEED **Torque:** 12,000 FT-LB
Hex Size: 2 5/8
Winch Type: TURRET MOUNT **Capacity:** 15,000 LBS
Tool Circuit: AUX AT REAR
Controls: SINGLE STICK T
Attachment: TRANSFERABLE POLE CLAW
Upper Controls: N **Insulated Boom:** Y **Radio Remote:** N
Standup Controls: N **Hose Reel:** Y

DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 94.5 **Length:** 308 **Width:** 96.7
GVWR: 25,999 **Unladen:** 25,480LBS **Tow Capacity:** 7520
Axle Capacity: 12,000LBS front / 21,000LBS rear
Wheelbase: 194 WB / 120 CA **Tire Size:** 11R22.5
Tread Front/Rear: **Tread Updated:**
PTO Hours: 2500
Engine Hours: 7,745 **Hours Updated:** 6/3/2020
Miles: 90,952 **Miles Updated:** 06/03/2020

Insurance Value: \$93,100.00

Additional Spec Information:

08 47' TEREX COMM 4047; 08 FORD F750 B0115257 EQUIP DESC: PEDESTAL & TURNTABLE, 50-GAL HYD OIL RESERVOIR, REMOTE SENSOR BRACKET, STOP/START AT COMMAND POST, BOOM REST, STEEL FIRST & SECOND BOOM SECTIONS, FIBERGLASS HYD THIRD, DUAL LIFT CYLINDERS, BOOM INTERLOCK TRUCK DESC: ICC REAR BUMPER, 2 WHEEL CHOCKS, B/U ALARM, FRONT TOW HOOKS, A/C, AM/FM, GRAB HANDLES, 30 TAILSHELF, 7-LAMP LIGHT BAR AT REAR, (4) OUTRIGGER PADS W/STORAGE, PUSH BUTTON THROTTLE, ENGINE START/STOP AT REAR, TOOL OUTLETS & COUPLERS AT REAR, B/U ALARM, (2) AMBER STROBE LIGHTS, 7-TON SWIVEL HOOK, FIRE EXTINGUISHER, TRIANGLE REFLECTOR KIT, HWY FLARE KIT, GROUND CABLE, 6-PRONG TRLR SOCKET, DOT INSPECTION, 50 GALLON HYD OIL RESERVOIR, 50' COPPER GROUNDING CABLE, CHASSIS FRAME REINFORCEMENTS, SHEAR BALL BEARING ROTATION, REMOTE SENSOR BRACKET, RUBBER AUX REAR SPRINGS, 45. GAL FUEL TANK, 7-PRONG TRLR SOCKET, LAMINATED WOOD OUTRIGGER PAD 24X24X2-1/4 W/ROPE HANDLE, 100X1-1/8 SAMSON UNCOATED STABLE BRAID ROPE

