



**B0116056 - 2012 TEREX COMMANDER 4047; 2012 INTERNATIONAL 7300 4X4**

Warehouse: N93 - NRU - NESCO -ST PAUL,MN

**CHASSIS SPECIFICATIONS**

**VIN:** 1HTWBAAN6DJ051199  
**Engine Make / HP:** MAXXFORCE DT / 245  
**Transmission:** ALLISON 3500RDS 5-SPEED A  
**Brakes:** AIR  
**Hitch:** 20 TON PINTLE HOOK  
**Winch Location:** N/A **Capacity:** N/A  
**Drive Type:** ALL WHEEL DRIVE **Fuel Type:** DIESEL **Rail Gear:** Y  
**Rail Gear Type:**

**EQUIPMENT SPECIFICATIONS**

**Serial Number:** 2120246261  
**Boom Capacity:** 24,630LBS  
**Bucket:** 24X24X42 1-MAN **Capacity:** 300LBS  
**Rotation:** CONTINUOUS  
**Outrigger(s):** (2) SETS A FRAME  
**Mount:** OVER REAR AXLE  
**Body:** UTILITY LINE  
**Sheave Height:** 47"  
**Auger:** 18 DIRT TOOTH  
**Dig Speed:** 2-SPEED **Torque:** 12,000 FT-LB  
**Hex Size:** 2 5/8  
**Winch Type:** TURRET MOUNT **Capacity:** 15,000LBS  
**Tool Circuit:** AUX BELOW ROTATION  
**Controls:** SINGLE STICK T  
**Attachment:** TRANSFERABLE POLE CLAW  
**Upper Controls:** Y **Insulated Boom:** Y **Radio Remote:** N  
**Standup Controls:** N **Hose Reel:** Y

**DIMENSIONS / MILES / HOURS / WEIGHTS**

**Height:** 12' 7" **Length:** 25' 8" **Width:** 8' 6"  
**GVWR:** 33,000 **Unladen:** 29,340LBS **Tow Capacity:** 3,660LBS  
**Axle Capacity:** 14,000LBS front / 19,000LBS rear  
**Wheelbase:** 199 WB / 120 CA **Tire Size:** 12R22.5  
**Tread Front/Rear:** 16/32; 10/32 **Tread Updated:** 8/16  
**PTO Hours:** 2238  
**Engine Hours:** 4,833 **Hours Updated:** 12/16/2019  
**Miles:** 79,961 **Miles Updated:** 12/16/2019

**Insurance Value: \$119,900.00**

**Additional Spec Information:**

RG - 12 47' TEREX COMM 4047; 13 IH 7300 4X4 B0116056 EQUIP DESC: PEDESTAL & TURNTABLE, DUAL LIFT CYLINDERS, STEEL LWR & INTERMEDIATE BOOM, FIBERGLASS HYD UPPER BOOM, BOOM INTERLOCK, COMBINED SPEED HYD SYSTEM, 50-GAL HYD OIL RESERVOIR, REMOTE SENSOR BRACKET, STOP/START AT CONTROL STATION, CURBSIDE COMMAND POST LOCATION, INSULATED PLATFORM LINER & VINYL PLATFORM COVER, CURBSIDE PLATFORM CONTROL LOCATION, INSULATED ENGINE STOP/START, AUX LET DOWN, STREETSIDE DIGGER LOCATION, POLE GUIDE FOR TRANSFERABLE POLE BUDDY, POLE GUIDE INTERLOCK FOR TRANSFERABLE POLE GUIDE, HOP, ADJ FLOW DIVIDER FOR AUX TOOL OUTLETS BELOW ROTATION, CONTROLS FOR 2 SETS OUTRIGGERS & AUX TOOL OUTLETS BELOW ROTATION, 4 OUTRIGGER PADS W/ROPE HANDLE, 4 RUBBER WHEEL CHOCKS W/EYE BOLT, BRACKET FOR STORING GROUNDING CABLE, 2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING, 50' MULTI-STRAND FLEXIBLE COPPER CABLE, 3 GROUNDING LUGS, 2 FERRULES & GROUNDING CLAMP, BOOM REST FOR DIGGER, DIGGER 2ND POSITION BOOM REST, POLE CARRIER, G

