



**B0116189 - 2012 N/A N/A; 2012 SDP EZ HAULER 5500**

Warehouse: N85 - NRU- CHEROKEE- CHATTANOOGA, TN

**CHASSIS SPECIFICATIONS**

**VIN:** 1S9LT2128C1313822  
**Engine Make / HP:** YANMAR / 36.3  
**Transmission:** HYDROSTATIC DRIVE  
**Brakes:** ELECTRIC  
**Track Type:** RUBBER  
**Hitch:** LUNETTE EYE  
**Winch Location:** N/A **Capacity:** N/A  
**Fuel Type:** DIESEL

**EQUIPMENT SPECIFICATIONS**

**Serial Number:** 101958881374  
**Boom Capacity:** 5,500LBS  
**Bucket:** 24X24X42 1-MAN **Capacity:** 300 LBS  
**Rotation:** CONTINUOUS  
**Outtrigger(s):** (2) SETS RADIAL  
**Mount:** TRACK  
**Body:** TRACK UNIT  
**Sheave Height:** 43'  
**Auger:** 18  
**Dig Speed:** 1-SPEED **Torque:** 3,500 FT-LB  
**Hex Size:** 2 5/8  
**Winch Type:** PLANETARY **Capacity:** 5,500LBS  
**Tool Circuit:** AUX BELOW ROTATION  
**Controls:** JOYSTICK/LEVER  
**Attachment:** PIN ON BUCKET  
**Upper Controls:** Y **Radio Remote:** Y **Standup Controls:** Y  
**Hose Reel:** Y

**DIMENSIONS / MILES / HOURS / WEIGHTS**

**Height:** **Length:** 15' 9" **Width:** 35.5  
**GWWR:** 16,000 **Unladen:** 12,020LBS **Tow Capacity:** 12,800LBS  
**PTO Hours:** 1099  
**Engine Hours:** 1,298 **Hours Updated:** 07/08/2019

**Insurance Value: \$47,900.00**

**Additional Specs:**

12 SDP EZ HAULTRACK5500; 11 SDP 7600 TRLR B0116189 EQUIP DESC: SELF STORING AUGER, HYD 3RD STAGE BOOM, POLE GUIDE, 3-POSITION DETENTED, 4-WAY MANUAL LEVER OPERATED HYD VALVE RELIEF BOTH PORTS, ADJUSTABLE FROM 1500-3000 PSI, HYD DIVERTER/SELECTOR VALVE W/#10 SAE PORTS, 1.5X4 HYD CYLINDER POLE GUIDE, TRACK INTERLOCK SAFETY SYSTEM, 12V DIRECTIONAL CONTROL VALVE FOR DUMP SYSTEM, 19 CC PER REVOLUTION HYD GEAR PUMP W/3000 PSI PRESET RELIEF VALVE, ALL EXTENSIONS HYD & AUGER MOUNTING & STORAGE BRACKET, ELITE SERIES RADIO TRANSMITTER, CRANE RECEIVER, MATED CRANE HARNESS, WINCH ROPE, 7' LONG 11 WIDE TRACKS 35.5 CLOSED X 51 EXTENDED, HYD POLE GUIDE, COIL CORD 12 V CHARGER FOR THE ORANGE REMOTE JOYSTICK TRANSMITTER, UNIVERSAL CHARGER FOR REMOTE TRANSMITTER, 25 FT CABLE FOR CAN/CHARGER FOR ORANGE JOYSTICK REMOTE CONTROL TRANSMITTER, CARBIDE TEETH, WIND UP STUD (4 FROM GUIDE), FISH TAIL POINT, 5' HEX VARIABLE LENGTH EXTENSION, 33 RPM @ 3500' # TORQUE AUGER DRIVE HEAD, REMOTE ENGINE HI

