



**B0117342 - 2011 TEREX XL-4045; 2013 FREIGHTLINER M2 106 4X4**

Warehouse: N08 - NRU - TEREX - CHARLOTTE NC

**CHASSIS SPECIFICATIONS**

**VIN:** 1FVDCXDT6DHFF7804  
**Engine Make / HP:** 6.7L CUMMINS ISB / 250  
**Transmission:** ALLISON 3500RDS 5-SPEED A  
**Brakes:** AIR  
**Hitch:** 15 TON PINTLE HOOK  
**Winch Location:** N/A **Capacity:** N/A  
**Drive Type:** ALL WHEEL DRIVE **Fuel Type:** DIESEL **Rail Gear:** N  
**Rail Gear Type:**



**EQUIPMENT SPECIFICATIONS**

**Serial Number:** 2111146090  
**Boom Capacity:** 34,660LBS  
**Bucket:** 24X24X42 SINGLE **Capacity:** 300LBS  
**Rotation:** CONTINUOUS  
**Outrigger(s):** 2 SETS A FRAME  
**Mount:** OVER REAR AXLE  
**Body:** FLATBED W/T BOX  
**Sheave Height:** 45'  
**Auger:** 18 CARBIDE  
**Dig Speed:** 2-SPEED **Torque:** 12,000LBS  
**Hex Size:** 2 5/8  
**Winch Type:** TURRET MOUNT **Capacity:** 15,000LBS  
**Tool Circuit:** HYD AT PLATFORM  
**Controls:** MULTI JOYSTICK  
**Attachment:** TRANSFERABLE POLE CLAW  
**Upper Controls:** Y **Insulated Boom:** Y **Radio Remote:** N  
**Standup Controls:** Y **Hose Reel:** Y



**DIMENSIONS / MILES / HOURS / WEIGHTS**

**Height:** 13' 2" **Length:** 25' 11" **Width:** 8' 6"  
**GVWR:** 33,000 **Unladen:** 28,180LBS **Tow Capacity:** 4820  
**Axle Capacity:** 14,000LBS front / 21,000LBS rear  
**Wheelbase:** 190 WB / 120 CA **Tire Size:** 12R22.5  
**Tread Front/Rear:** 21/32: 18/32 **Tread Updated:** 04/12/2018  
**PTO Hours:** 1517  
**Engine Hours:** 4,641 **Hours Updated:** 5/7/2020  
**Miles:** 58,251 **Miles Updated:** 05/07/2020



**Insurance Value: \$79,900.00**

**Additional Spec Information:**

11 45' TEREX XL4045; 13 FL M2106 4X4 B0117342 EQUIP DESC: ELEVATION FROM +80 DEGREES ABOVE HORIZONTAL TO -20 DEGREES BELOW HORIZONTAL, PEDESTAL & TURNABLE, STEEL LWR & INTERMEDIATE BOOM, FIBERGLASS HYD UPPER BOOM, BOOM INTERLOCK, 3000PSI HYD SYSTEM, 50-GAL HYD OIL RESERVOIR, STAND BESIDE PEDESTAL MTD DUAL CONTROL STATION, REMOTE SENSOR BRACKET, STOP/START AT EACH HANDLE RACK STATION, INSULATED PLATFORM LINER, INSULATED ENGINE THROTTLE ADVANCE AT PLATFORM, INSULATED ENGINE STOP/START, BOOM STOW PROTECTION FOR CONTROLS BELOW ROTATION, HOP, CHASSIS CONTROLLER, 1-1/8 X 100' STABLE BRAID UNCOATED ROPE, CONTROLS FOR 2 SETS OUTRIGGERS & AUX TOOL OUTLETS BELOW ROTATION, 2-PART SHEAVE ASSY W/12 TON CAPACITY, 4 OUTRIGGER PADS W/ROPE HANDLE, 4 RUBBER WHEEL CHOCKS W/EYE BOLT, BRACKET FOR STORING GROUNDING CABLE, 2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING, 50' MULTI-STRAND FLEXIBLE COPPER CABLE, 3 GROUNDING LUGS, 2 FERRULES & GROUNDING CLAMP, BOOM REST FOR DIGGER, 6 TON SWIVEL HOOK