



A0116696 - 60' 2012 TEREX TC-55; 2012 FORD F750 4X2

Warehouse: N56 - NRU - NESCO - ALVARADO, TX

CHASSIS SPECIFICATIONS

VIN: 3FRXF7FK9CV297296
Engine Make / HP: 6.7L CUMMINS I-6 / 260
Transmission: ALLISON 3000RDS 5-SPEED A
Brakes: AIR
Hitch: 15 TON PINTLE HOOK
Winch Location: N/A **Capacity:** N/A
Drive Type: NON-AWD **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:



EQUIPMENT SPECIFICATIONS

Serial Number: 2121047743
Working Height: 60' **Capacity:** 700 LBS
Bucket: 24X48X42 2-MAN
Certified Kv: 46KV CAT C
Rotation: CONTINUOUS
Outrigger(s): (2) SETS A FRAME
Mount: OVER REAR AXLE
Tool Circuit: DUAL HYD AT PLATFORM
Controls: SINGLE STICK
Body: UTILITY LINE
Winch/Jib: HYD EXT JIB WINCH **Capacity:** 2,000LBS
Additional: N/A
Over Center: N **Telescoping:** N **Upper Controls:** Y
Rotator: Y **Material Handler:** Y **Insulated Boom:** Y

DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 12' 0" **Length:** 30' 3" **Width:** 8' 6"
GVWR: 33,000 **Unladen:** 23,520LBS **Tow Capacity:**
Axle Capacity: 13,200LBS front / 21,000LBS rear
Wheelbase: 194 WB / 120 CA **Tire Size:** 11R22.5
Tread Front/Rear: 100% **Tread Updated:** 12/12
PTO Hours: 829
Engine Hours: 7,494 **Hours Updated:** 12/18/2019
Miles: 46,891 **Miles Updated:** 03/09/2020

Selling Price: \$69,500.00

Additional Specs:

60' 12 TEREX TC55-MH; 12 FORD F750 4X2 A0116696 EQUIP DESC: LWR CONTROLS ON TURNABLE, ENGINE THROTTLE ADVANCE, PLATFORM LEVELING, HYD PLATFORM TILT, BOOM COMPENSATION SYSTEM, BOOM INTERLOCK, ROTATION BEARING IS A HEAVY DUTY SHEAR BALL BEARING UTILIZING POLISHED ALLOY STEEL BALLS, CLOSED-CENTER PARALLEL-CIRCUIT 2500PSI HYD SYSTEM, 35-GAL HYD OIL RESERVOIR, INSULATED PLATFORM LINER & VINYL PLATFORM COVER, PLATFORM REST SADDLE W/A PADDED REST, INSULATED ENGINE STOP/START, CHASSIS CONTROLLER, COMPONENTS TO MEET ANSI CATEGORY B 69KV RATING, CONTROLS FOR 2 SETS OUTRIGGERS W/AUX TOOL OUTLETS, AUTOMATIC BOOM LATCH, B/U ALARM, 4 OUTRIGGER PADS W/ROPE HANDLE, 4 RUBBER WHEEL CHOCKS W/EYE BOLT, BRACKET FOR STORING GROUNDING CABLE, 2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING, 50' MULTI-

STRAND FLEXIBLE COPPER CABLE, 3 GROUNDING LUGS, 2 FERRULES & GROUNDING CLAMP, 2 AMBER STROBE LIGHTS & BRANCH
GUARD TRUCK DESC: 7-LAMP DOT LIGHTING PKG, REMOTE ENGINE STOP/START & 2-SPEED CONTROL FROM REA