



A0119793 - 60' 2014 TEREX TC-55; 2015 FORD F750 4X2

Warehouse: N42 - NRU - TEREX - MOUNTVILLE, PATE

CHASSIS SPECIFICATIONS

VIN: 3FRXF7FK8FV624422
Engine Make / HP: 6.7L CUMMINS I-6 OHV / 260
Transmission: ALLISON 3000RDS 6-SPEED A
Brakes: AIR
Hitch: 15 TON PINTLE HOOK
Winch Location: N/A
Drive Type: NON-AWD
Fuel Type: DIESEL
Rail Gear Type:
Capacity: N/A
Rail Gear: N



EQUIPMENT SPECIFICATIONS

Serial Number: 2141052710
Working Height: 60'
Bucket: 24X48X42 2-MAN
Certified Kv: 46KV CAT C
Rotation: CONTINUOUS
Outrigger(s): (2) SETS A FRAME
Mount: OVER REAR AXLE
Tool Circuit: DUAL HYD AT PLATFORM
Controls: SINGLE STICK
Body: UTILITY LINE
Winch/Jib: HYD EXT JIB WINCH
Additional: N/A
Over Center: N
Telescoping: N
Rotator: Y
Material Handler: Y
Capacity: 700 LBS
Capacity: 2,000LBS
Upper Controls: Y
Insulated Boom: Y



DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 12'3" **Length:** 30'4" **Width:** 7'10"
GVWR: 33,000 **Unladen:** 24,220LBS **Tow Capacity:**
Axle Capacity: 12,000LBS front / 21,000LBS rear
Wheelbase: 194 WB / 120 CA **Tire Size:** 11R22.5
Tread Front/Rear: 22/32; 28/32 **Tread Updated:** 8/15
PTO Hours: 1678
Engine Hours: 2,718 **Hours Updated:** 3/16/2020
Miles: 67,934 **Miles Updated:** 03/16/2020



Selling Price: \$79,500.00

Additional Specs:

60' 14 TEREX TC55-MH; 15 FORD F750 XL 4X2 A0119793 EQUIP DESC: NON-OVERCENTER, LWR CONTROLS ON TURNTABLE, ENGINE THROTTLE ADVANCE, PLATFORM LEVELING, HYD PLATFORM TILT, BOOM COMPENSATION SYSTEM, BOOM INTERLOCK, ROTATION BEARING IS A HD SHEAR BALL BEARING UTILIZING POLISHED ALLOY STEEL BALLS, 2500PSI CLOSED CENTER PARALLEL CIRCUIT HYD SYSTEM, 35-GAL HYD OIL RESERVOIR, INSULATED PLATFORM LINER & VINYL PLATFORM COVER, AUX LET DOWN FOR USE W/CLOSED CENTER HYDRAULICS, INSULATED ENGINE STOP/START, PLATFORM REST SADDLE W/A PADDED REST, CHASSIS CONTROLLER, 75' X 1/2 WINCH LOAD LINE, CONTROLS FOR 2 SETS OUTRIGGERS W/AUX TOOL OUTLETS, AUTOMATIC BOOM LATCH, B/U ALARM, 4 OUTRIGGER PADS W/ROPE HANDLE, 4 RUBBER WHEEL CHOCKS W/EYE BOLT, BRACKET FOR STORING GROUNDING CABLE, 2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING, 50' MULTI-STRAND FLEXIBLE COPPER CABLE, 3 GROUNDING LUGS, 2 FERRULES & GROUNDING CLAMP, GROUNDING LOOP KIT, BOOM REST FOR AERIAL TRUCK DESC: 7-LAMP DOT LIGHTING PKG, 2 AMBER STRO

