



**G0118795 - 2013 SHERMAN & REILLY T-7212**

Warehouse: O26 - OR - CTEC - REGINA, SK

**EQUIPMENT SPECIFICATIONS**

**VIN:** 5DDKE2528E1006867\*00  
**Brakes:** AIR  
**Tire Size:** 275/70R22.5  
**Hitch:** 5TH WHEEL  
**Bullwheel Dia:** (2) SETS 72  
**Max Tension Capacity:** 12,000LBS  
**Attachment:** KALYN SIEBERT LB-2-20T TRLR

**DIMENSIONS / MILES / HOURS / WEIGHTS**

<b>Height:</b> 12'4"	<b>Length:</b> 35'	<b>Width:</b> 102
<b>GVWR:</b> 30,000		
<b>Unladen Weight:</b> 21,500LBS		
<b>Tread:</b> 22/32	<b>Tread Updated:</b> 8/13	

**Selling Price: \$342,500.00**



**Additional Specs:**

DBL BNDL BW TENS S&R T7212 13 G0118795 EQUIP DESC: TENSIONS 2 CONDUCTORS AT ONCE, SYNCHRONIZED TENSIONING, PROTECTED OFF-GROUND OPERATOR POSITION, HYDRAULICALLY DRIVEN BULLWHEELS, FULLY ENCLOSED SAFE-ZONE CAB, HEATING AND AIR CONDITIONING, DIGITAL CONTROLS, RECORDS/DISPLAYS TENSION AND DISTANCE, ELECTRONIC CONTROLS AND GAUGES, SELF-DIAGNOSTICS, PLANETARY GEARBOX, HYDRAULIC MOTOR W/SPRING-APPLIED HYD RELEASE BRAKE, MICROPROCESSOR-CONTROLLED MOTOR DRIVE, AUTO TENSIONING SYSTEM, PERMITTING MANUAL OVERRIDE, PULL-DRIVE MODE FOR REWINDING, 4MPH LINE SPEED, 1-1/8 GROOVE RADIUS, POLYURETHANE MINING MATERIAL, PLC MACHINE CONTROL WITH CAN-BUS TECHNOLOGY, REMOVABLE/REPLACEABLE MEMORY CARD, SELF-DIAGNOSTIC SYSTEM, PTO, (4) FAIRLEAD ROLLERS TRLR DESC: KALYN SIEBERT LB-20 TRLR, 2 HYDRAULIC FRONT JACK, 2 MANUAL NOSE JACKS, 2 HYDRAULIC VERTICAL CYLINDER REAR JACKS, SPLIT 12/24 VDC ELECTRICAL SYSTEM, US DOT-LED-12 VDC LIGHTING, CAB-TOB FLOOD LIGHTS, DUAL 12V BATTERIES, (4) 3/4 DIA COPPER-CLAD S