



A0114860 - 55' 2011 TEREX TL-50; 2012 INTERNATIONAL 4300 4X2
Warehouse: RNT - UNIT ON RENTAL

CHASSIS SPECIFICATIONS

VIN: 3HAMMAAN5CL434343
Engine Make / HP: MAXX FORCE DT / 245
Transmission: 5-SPEED AUTO
Brakes: AIR
Hitch: 15 TON PINTLE HOOK
Winch Location: **Capacity:**
Drive Type: NON-AWD **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:



EQUIPMENT SPECIFICATIONS

Serial Number: 2110343651
Working Height: 55' **Capacity:** 600 LBS
Bucket: 24X48X42 2-MAN
Certified Kv: 46KV CAT C
Rotation: CONTINUOUS
Outrigger(s): (2) SETS A FRAME
Mount: OVER REAR AXLE
Tool Circuit: DUAL HYD AT PLATFORM
Controls: SINGLE STICK
Body: UTILITY LINE
Additional:
Over Center: N **Telescoping:** Y **Upper Controls:** Y
Rotator: Y **Material Handler:** N **Insulated Boom:** Y



DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 11' 10" **Length:** 26' 6" **Width:** 8' 6"
GVWR: 33,000 **Unladen:** 22,020LBS **Tow Capacity:**
Axle Capacity: 13,000LBS front / 20,000LBS rear
Wheelbase: 187 WB / 120 CA **Tire Size:** 11R22.5
Tread Front/Rear: 9/32; 15/32 **Tread Updated:** 4/15/2020
PTO Hours: 3942
Engine Hours: 6,969 **Hours Updated:** 4/15/2020
Miles: 74,309 **Miles Updated:** 04/15/2020



Additional Specs:

55' 11 TEREX TL50P; 12 IH 4300 4X2 A0114860 EQUIP DESC: END MOUNT PLATFORM, PLATFORM LEVELING, UPPER CONTROLS, LWR BOOM ARTICULATION IS FROM 0 TO 87 DEGREES, UPPER BOOM HAS AN ARTICULATION OF -40 TO 75 DEGREES, ENGINE THROTTLE CONTROL IS PROVIDED AT THE UPPER CONTROLS, BOOM INTERLOCK, PEDESTAL, TURNTABLE, COUNTINUOUS UNRESTRICTED ROTATION, ROTATION BEARING IS A HEAVY-DUTY 'SHEAR-BALL' BEARING W/EXTERNAL GEAR TEETH, CATEGORY C DIELECTRICALLY TESTED & RATED FOR OPERATION UP TO 46,000 WORKING LINE VOLTAGE PER ANSI/SIA A92.2-2009, FULL PRESSURE, OPEN CENTER HYD SYSTEM, 20-GAL HYD OIL RESERVOIR, HYD PUMP, 58 PEDESTAL W/20 GAL INTERNAL TANK, HYD PLATFORM ROTATOR, INSULATED PLATFORM LINER, VINYL PLATFORM COVER, DUAL HYD TOOL OUTLETS AT PLATFORM, AUX LET DOWN, PLATFORM REST, INSULATED ENGINE STOP/START, TIE DOWN KIT, (1) SET UNDERSLUNG MODIFIED A-FRAME OUTRIGGERS, CONTROLS FOR 2-SETS OF OUTRIGGERS & AUXI TOOL OUTLETS, (4) LAMINATED WOOD OUTRIGGER PAD W/ROPE HANDLE, BRACKET FOR STORING GR