

**A0116286 - 55' 2012 TEREX TL-50; 2012 FORD F750 4X2**

Warehouse: W81 - WIP - NESCO - TALLAHASSEE, FL

**CHASSIS SPECIFICATIONS**

<b>VIN:</b>	3FRXF7FK4CV169242	
<b>Engine Make / HP:</b>	6.7L CUMMINS I-6 / 260	
<b>Transmission:</b>	5-SPEED AUTO	
<b>Brakes:</b>	AIR	
<b>Hitch:</b>	15 TON PINTLE HOOK	
<b>Winch Location:</b>	N/A	<b>Capacity:</b> N/A
<b>Drive Type:</b> NON-AWD	<b>Fuel Type:</b> DIESEL	<b>Rail Gear:</b> N
<b>Rail Gear Type:</b>		

**EQUIPMENT SPECIFICATIONS**

<b>Serial Number:</b>	2120747232	
<b>Working Height:</b>	55'	
<b>Bucket:</b>	24X48X42 2-MAN	<b>Capacity:</b> 600 LBS
<b>Certified Kv:</b>	46KV CAT C	
<b>Rotation:</b>	CONTINUOUS	
<b>Outrigger(s):</b>	(2) SETS A FRAME	
<b>Mount:</b>	OVER REAR AXLE	
<b>Tool Circuit:</b>	HYD AT PLATFORM	
<b>Controls:</b>	SINGLE STICK	
<b>Body:</b>	UTILITY LINE	
<b>Winch/Jib:</b>	HYD EXT JIB WINCH	<b>Capacity:</b> 1,000LBS
<b>Additional:</b>		
<b>Over Center:</b> N	<b>Telescoping:</b> Y	<b>Upper Controls:</b> Y
<b>Rotator:</b> Y	<b>Material Handler:</b> Y	<b>Insulated Boom:</b> Y

**DIMENSIONS / MILES / HOURS / WEIGHTS**

<b>Height:</b> 11' 11"	<b>Length:</b> 27' 4"	<b>Width:</b> 8' 6"
<b>GVWR:</b> 33,000	<b>Unladen:</b> 21,980LBS	<b>Tow Capacity:</b>
<b>Axle Capacity:</b>	13,200LBS front / 21,000LBS rear	
<b>Wheelbase:</b>	194 WB / 120 CA	<b>Tire Size:</b> 11R22.5
<b>Tread Front/Rear:</b>	15/32; 19/32	<b>Tread Updated:</b> 6/13
<b>PTO Hours:</b>	44	
<b>Engine Hours:</b>	2,975	<b>Hours Updated:</b> 7/22/2020
<b>Miles:</b>	24,114	<b>Miles Updated:</b> 12/11/2020

**Additional Specs:**

55' 12 TEREX TL50M; 12 FORD F750 4X2 A0116286 EQUIP DESC: END MOUNT PLATFORM, PLATFORM LEVELING, LWR CONTROLS ON TURNTABLE, ENGINE THROTTLE CONTROL AT UPPER CONTROLS, BOOM INTERLOCK, ROTATION BEARING IS A HEAVY DUTY SHEAR BALL BEARING W/EXTERNAL GEAR TEETH UTILIZING POLISHED ALLOY STEEL BALLS, FULL PRESSURE OPEN CENTER HYD SYSTEM, 20-GAL HYD OIL RESERVOIR, INSULATED PLATFORM LINER & VINYL PLATFORM COVER, AUX LET DOWN FOR USE W/OPEN CENTER HYDRAULICS, INSULATED ENGINE STOP/START, CHASSIS CONTROLLER, WINCH LEVELS W/PLATFORM (BUT DOES NOT ROTATE W/PLATFORM), MANUAL ARTICULATION FROM 0 TO 50 DEGREES, MINIMUM REACH OF 49 FROM THE PLATFORM SHAFT, SHEAVE HEAD CAN BE MANUALLY EXTENDED TO 56, JIB W/WINCH IS REMOVABLE & COMES W/SHIP LOOSE SOCKET TO STORE THE JIB/WINCH WHEN REMOVED, JIB INCLUDES 70' OF 1/2 WINCH ROPE & HOOK, CONTROLS FOR 2 SETS OUTRIGGERS & AUX TOOL OUTLETS, B/U ALARM, 4 OUTRIGGER PADS W/ROPE HANDLE, 4 RUBBER WHEEL CHOCKS W/EYE BOLT, BRACKET FOR STORING GROUNDING CABLE.