



B0115254 - 2008 TEREX COMMANDER 4047; 2008 FORD F750 4X2
Warehouse: W14 - WIP - TEREX - PORTLAND OR

CHASSIS SPECIFICATIONS

VIN: 3FRXF75T48V071572
Engine Make / HP: 7.2L CAT / 250
Transmission: 5-SPEED AUTO
Brakes: AIR
Hitch: 15 TON PINTLE
Winch Location: N/A **Capacity:** N/A
Drive Type: NON-AWD **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:
*** NOT C.A.R.B COMPLIANT ***



EQUIPMENT SPECIFICATIONS

Serial Number: 2080636949
Boom Capacity: 24630LB
Rotation: CONTINUOUS
Outrigger(s): 2 SETS A FRAME
Mount: OVER REAR AXLE
Body: UTILITY LINE
Sheave Height: 47'
Auger: 20 STEEL
Dig Speed: 2-SPEED **Torque:** 12,000 FT-LB
Hex Size: 2 5/8
Winch Type: TURRET MOUNT **Capacity:** 15,000LBS
Tool Circuit: AUX AT REAR
Controls: SINGLE STICK T
Attachment: TRANSFERABLE POLE CLAW
Upper Controls: N **Insulated Boom:** Y **Radio Remote:** N
Standup Controls: N **Hose Reel:** Y



DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 94.5 **Length:** 308 **Width:** 96.7
GVWR: 33,000 **Unladen:** 26,080LBS **Tow Capacity:** 6920
Axle Capacity: 12,000LBS front / 21,000LBS rear
Wheelbase: 194 WB / 120 CA **Tire Size:** 11R22.5
Tread Front/Rear: **Tread Updated:**
PTO Hours: 2545
Engine Hours: 5,688 **Hours Updated:** 10/2/2020
Miles: 70,899 **Miles Updated:** 10/02/2020



Additional Spec Information:

08 47' TEREX COMM 4047; 08 FORD F750 B0115254 EQUIP DESC: PEDESTAL & TURNTABLE, 50-GAL HYD OIL RESERVOIR, REMOTE SENSOR BRACKET, STOP/START AT COMMAND POST, BOOM REST, STEEL FIRST & SECOND BOOM SECTIONS, FIBERGLASS HYD THIRD, DUAL LIFT CYLINDERS, BOOM INTERLOCK TRUCK DESC: ICC REAR BUMPER, 2 WHEEL CHOCKS, B/U ALARM, FRONT TOW HOOKS, A/C, AM/FM, GRAB HANDLES, 30 TAILSHELF, 7-LAMP LIGHT BAR AT REAR, (4) OUTRIGGER PADS W/STORAGE, PUSH BUTTON THROTTLE, ENGINE START/STOP AT REAR, TOOL OUTLETS & COUPLERS AT REAR, B/U ALARM, (2) AMBER STROBE LIGHTS, 7-TON SWIVEL HOOK, FIRE EXTINGUISHER, TRIANGLE REFLECTOR KIT, HWY FLARE KIT, GROUND CABLE, 6-PRONG TRLR SOCKET, DOT INSPECTION, 50 GALLON HYD OIL RESERVOIR, 50' COPPER GROUNDING CABLE, CHASSIS FRAME REINFORCEMENTS, SHEAR BALL BEARING ROTATION, 4-WHEEL ABS, REMOTE SENSOR BRACKET, RUBBER AUX REAR SPRINGS, 45. GAL FUEL TANK, 7-PRONG TRLR SOCKET, LAMINATED WOOD OUTRIGGER PAD 24X24X2-1/4 W/ROPE HANDLE, 100X1-1/8 SAMSON UNCOATED STABLE BRA