



B0117340 - 2011 TEREX XL-4045; 2013 FREIGHTLINER M2 106 4X4
Warehouse: RNT - UNIT ON RENTAL

CHASSIS SPECIFICATIONS

VIN: 3ALDCXDT3DDBM5219
Engine Make / HP: 6.7L CUMMINS ISB / 250
Transmission: ALLISON 3500RDS 5-SPEED A
Brakes: AIR
Hitch: 15 TON PINTLE HOOK
Winch Location: N/A **Capacity:** N/A
Drive Type: ALL WHEEL DRIVE **Fuel Type:** DIESEL **Rail Gear:** N
Rail Gear Type:



EQUIPMENT SPECIFICATIONS

Serial Number: 2111145979
Boom Capacity: 34,660LBS
Bucket: 24X24X42 SINGLE **Capacity:** 300LBS
Rotation: CONTINUOUS
Outrigger(s): 2 SETS A FRAME
Mount: OVER REAR AXLE
Body: FLATBED W/T BOX
Sheave Height: 45'
Auger: 18 CARBIDE
Dig Speed: 2-SPEED **Torque:** 12,000LBS
Hex Size: 2 5/8
Winch Type: TURRET MOUNT **Capacity:** 15,000LBS
Tool Circuit: HYD AT PLATFORM
Controls: MULTI JOYSTICK
Attachment: TRANSFERABLE POLE CLAW
Upper Controls: Y **Insulated Boom:** Y **Radio Remote:** N
Standup Controls: Y **Hose Reel:** Y



DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 13' 2" **Length:** 26' 0" **Width:** 8' 6"
GVWR: 33,000 **Unladen:** 28,160LBS **Tow Capacity:** 4840
Axle Capacity: 14,000LBS front / 21,000LBS rear
Wheelbase: 190 WB / 120 CA **Tire Size:** 12R22.5
Tread Front/Rear: 100% **Tread Updated:** 1/13
PTO Hours: 3398
Engine Hours: 3,367 **Hours Updated:** 6/15/2020
Miles: 39,490 **Miles Updated:** 06/15/2020



Additional Spec Information:

11 45' TEREX XL4045; 13 FL M2106 4X4 B0117340 EQUIP DESC: ELEVATION FROM +80 DEGREES ABOVE HORIZONTAL TO -20 DEGREES BELOW HORIZONTAL, PEDESTAL & TURNTABLE, STEEL LWR & INTERMEDIATE BOOM, FIBERGLASS HYD UPPER BOOM, BOOM INTERLOCK, 3000PSI HYD SYSTEM, 50-GAL HYD OIL RESERVOIR, STAND BESIDE PEDESTAL MTD DUAL CONTROL STATION, REMOTE SENSOR BRACKET, STOP/START AT EACH HANDLE RACK STATION, 2 INSULATED PLATFORM LINERS, INSULATED ENGINE THROTTLE ADVANCE AT PLATFORM, INSULATED ENGINE STOP/START, BOOM STOW PROTECTION FOR CONTROLS BELOW ROTATION, HOP, CHASSIS CONTROLLER, 1-1/8 X 100' STABLE BRAID UNCOATED ROPE, CONTROLS FOR 2 SETS OUTRIGGERS & AUX TOOL OUTLETS BELOW ROTATION, 2-PART SHEAVE ASSY W/12 TON CAPACITY, 4 OUTRIGGER PADS W/ROPE HANDLE, 4 RUBBER WHEEL CHOCKS W/EYE BOLT, BRACKET FOR STORING GROUNDING CABLE, 2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING, 50' MULTI-STRAND FLEXIBLE COPPER CABLE, 3 GROUNDING LUGS, 2 FERRULES & GROUNDING CLAMP, BOOM REST FOR DIGGER, 6 TON SWIVEL HOOK