

**G0116616 - 2012 TSE DPT40B**

Warehouse: RNT - UNIT ON RENTAL

**EQUIPMENT SPECIFICATIONS**

**VIN:** 1T92C1528CS268070  
**Engine Make:** JD 4024T-IT4; 49 HP  
**Brakes:** ELECTRIC  
**Tire Size:** ST235/80R16  
**Hitch:** LUNETTE EYE  
**Max Reel Dia:** 72  
**Max Reel Width:** 54  
**Max Reel Weight:** 6,000LBS  
**Max Pulling Capacity:** 4,350LBS  
**Max Rope/Cable:** 5/8 X 10,000 TENEX

**Rope/Cable Length and Last Updated**

<b>Red Drum:</b>		<b>Red Drum Updated:</b>
<b>Blue Drum:</b>	12100'	<b>Blue Drum Updated:</b> 1/11/2020
<b>Green Drum:</b>		<b>Green Drum Updated:</b>
<b>Yellow Drum:</b>		<b>Yellow Drum Updated:</b>
<b>Orange Drum:</b>		<b>Orange Drum Updated:</b>
<b>Black Drum:</b>		<b>Black Drum Updated:</b>

**DIMENSIONS / MILES / HOURS / WEIGHTS**

<b>Height:</b> 70	<b>Length:</b> 183	<b>Width:</b> 89
<b>GVWR:</b>	13,200	
<b>Unladen Weight:</b>	4,800LBS	
<b>Engine Hours:</b>	3,647	<b>Hours Updated:</b> 1/10/2020
<b>Tread:</b>	6/32	<b>Tread Updated:</b> 10/16

**Additional Specs:**

PULLER/TENS TSE DPT40B 12 G0116616 EQUIP DESC: TUBULAR STEEL FRAME, CONTINUOUS TORQUE RATING OF 70,000 IN-LBS, CONTINUOUS LINE PULL RATING OF 4,350 W/6,000 FT OF 5/8 ROPE ON THE REEL, 2-5/8 DIA REEL SHAFT, REEL DRIVE ARM W/2 ADJUSTABLE DRIVE PINS, PISTON TYPE HYD MOTOR, MANUAL HOLDING BRAKE CONTROL, HYD OIL COOLER, 18-GAL HYD RESERVOIR, HYD PRESSURE GAUGE, ADJUSTABLE LINE PULL/TENSION CONTROL, 19-GAL FUEL TANK, SAFETY CHAINS W/HOOKS, SHAFT MTD OVERSPIN BRAKE, HYD OVERHEAD LEVELWIND, 44 OVERHEAD PULLING REEL

