



G0118962 - 2013 SHERMAN & REILLY T-7212

Warehouse: W26 - WIP - CTEC - REGINA, SK

EQUIPMENT SPECIFICATIONS

VIN: 5DDKE2524D1006444*00
Brakes: AIR
Tire Size: 275/70R22.5
Hitch: 5TH WHEEL
Bullwheel Dia: (2) SETS 72
Max Tension Capacity: 12,000LBS
Attachment: KALYN SIEBERT LB-2-20T TRLR

DIMENSIONS / MILES / HOURS / WEIGHTS

Height: 12'4" **Length:** 19'6" **Width:** 102"
GVWR: 30,000
Unladen Weight: 21,500LBS
Tread: **Tread Updated:**



Additional Specs:

DBL BN DL BW TENS S&R T7212 14; KALYN SIEBERT TRLR 12 G0118962 EQUIP DESC: ARCTIC KIT, TENSIONS 2 CONDUCTORS AT ONCE, SYNCHRONIZED TENSIONING, PROTECTED OFF-GROUND OPERATOR POSITION, HYDRAULICALLY DRIVEN BULLWHEELS, FULLY ENCLOSED SAFE-ZONE CAB, HEATING AND AIR CONDITIONING, DIGITAL CONTROLS, RECORDS/DISPLAYS TENSION AND DISTANCE, ELECTRONIC CONTROLS AND GAUGES, SELF-DIAGNOSTICS, PLANETARY GEARBOX, HYDRAULIC MOTOR W/SPRING-APPLIED HYD RELEASE BRAKE, MICROPROCESSOR-CONTROLLED MOTOR DRIVE, AUTO TENSIONING SYSTEM, PERMITTING MANUAL OVERRIDE, PULL-DRIVE MODE FOR REWINDING, 4MPH LINE SPEED, 1-1/8 GROOVE RADIUS, POLYURETHANE MINING MATERIAL, PLC MACHINE CONTROL WITH CAN-BUS TECHNOLOGY, REMOVABLE/REPLACEABLE MEMORY CARD, SELF-DIAGNOSTIC SYSTEM, PTO, (4) FAIRLEAD ROLLERS TRLR DESC: KALYN SIEBERT LB-20 TRLR, 2 HYDRAULIC FRONT JACK, 2 MANUAL NOSE JACKS, 2 HYDRAULIC VERTICAL CYLINDER REAR JACKS, SPLIT 12/24 VDC ELECTRICAL SYSTEM, US DOT-LED-12 VDC LIGHTING, CAB-TOB FLOOD LIGHTS, DUAL 12