



G0119045 - 2014 SHERMAN & REILLY PTR-7230  
Warehouse: W37 - WIP - NESCO ONTARIO, CA

**EQUIPMENT SPECIFICATIONS**

VIN: 5DDKE2225E1007155\*00  
 Engine Make: WATER COOLED DIESEL; 268 HP  
**\* NOT C.A.R.B COMPLIANT \***  
 Brakes: AIR  
 Tire Size: 275/70R22.5  
 Hitch: 5TH WHEEL  
 Max Reel Dia: 120  
 Max Reel Width: 60  
 Max Reel Weight: NA  
 Max Pulling Capacity: 30,000LBS  
 Max Rope/Cable: 22,000' OF 0.84 UNITREX

**Rope/Cable Length and Last Updated**

Red Drum:	Red Drum Updated:
Blue Drum:	Blue Drum Updated:
Green Drum:	Green Drum Updated:
Yellow Drum:	Yellow Drum Updated:
Orange Drum:	Orange Drum Updated:
Black Drum:	Black Drum Updated:

**DIMENSIONS / MILES / HOURS / WEIGHTS**

Height: 8' 6	Length: 33'	Width: 8' 6
GVWR: 65,200		
Unladen Weight: 29,000LBS		
Engine Hours: 38	Hours Updated: 02/27/2019	
Tread: 20/32	Tread Updated: 5/16	

**Additional Specs:**

PULLER/TENS S&R PTR7230S 14; KAYLIN SIEBERT TRAILER 14 G0119045 \*\*\* TO BE RENTED WITH G0119046 \*\*\* EQUIP DESC: ARCTIC KIT, 25,000' UNITREX ROPE, PULLER/TENSIONER/RECONDUCTOR. 30,000LBS PULLING FORCE, 12,000LBS TENSIONING CAPACITY MAX, 20,000LBS RECONDUCTORING CAPACITY, 4 MPH LINE SPEED, 72 BULLWHEEL DIA, 6 GROOVES PER BULLWHEEL, 1 3/16 GROOVE RADIUS, NEOPRENE GROOVE LINING, MOLDED AND REPLACEABLE, HYDRAULIC TENSION BRAKE, AUTOMATIC BRAKE CONTROL, HYDRAULIC DRIVE SYSTEM, HYDRAULIC AUTOMATIC LEVELWIND, 20 GALLON HYDRAULIC TANK, 12 GALLON FUEL CAPACITY, ADJUSTABLE FAIRLEAD ROLLERS, FAIL SAFE BRAKE, SAFE ZONE ECLOSED CAB WITH AC AND HEAT, STEEL FRAME CONSTRUCTION TRAILER DESC: AIR RIDE SUSPENSION, TANDEM AXLE, AIR BRAKES, 5TH WHEEL ATTACHMENT, SAFETY CHAINS, CORNER STABILITY JACKS, 12V/24V SPLIT ELECTRICAL SYSTEM, US DOT/LED/ 12 VDC LIGHTING, CAB TOP LED FLOODS, 12V DUAL BATTERY, 3/4 GROUNDING COPPER CLAD GROUND LOOPS

